Tool Make & Model

Semitool SRD 4300-S

Tool Configuration / Specifications

* Newly Re-Manufactured/Refurbished Semitool SRD
* Semitool 4300-5 Spin Rinser Dryer
* Single-Stack configuration
* System to be refurbished
* Polypropylene cabinet
* Up to 8" process capability
* Brushless motor
* New Teflon DI and N2 lines
* New color-coded pneumatic tubing
* Bowls to be electropolished
* Labyrinth Seal design
* 220V ready system
* QD single bolt rotor design

Refurbishment includes but not limited to: Electropolish metal surfaces

* Spin dryer bowl
* Nitrogen manifold
* Mounting brackets

New Components {the following components are replaced with new as needed)

* New Gaskets & 0-Rings for
* D.I. Water Manifold
* Nitrogen manifold
* Rear bowl seal
* Door seal
* New Vibration dampers
* New Color-coded pneumatic tubing
* New Teflon lines for N2
* New Teflon lines for D.I.
* New DI Nozzles
* New N2 Filter

Includes:

* DI resistivity
* Static-eliminator
* Water recirculation
* Rotor, 200mm, CKPlas
* Balanced 0 - 2 5 substrates

Browse our site at www.moov.co

The information contained in this data sheet is, to our knowledge, accurate. We do not warrant the completeness or accuracy of the information contained herein. Any offer by you to purchase the equipment described in this data sheet shall be subject to the terms and conditions of sale.