Standard	Qty
300mm Fully Automatic Dicing saw including: - 1.2 KW facing dual-spindle -Touch panel LCD screen for easy operation - CE-Mark and EMC conformity - Standard Accessories - Exporting packing	1
Option	
Starter Kit For 2-Inch Hub Mount	1
Tape Frame (DTF2-12 Type- Frame Thicknessl.5mm)	10
Cassette (DTC212 type 300mm 13-slot standard cassette)	1
Elevator Cover	1
Spare Porous Chuck Table For (1)200 mm	1
Spare Spinner Table ForC1>200 mm	1
Spinner Atomizing Nozzle TypeHC2 (HighClean version 2 type)	1
Non-Contact Setup	1
General Tool Set	1
Lifting Jig Set	1
Export Packing Hardware	1
Power Cable Transformer specification(AC 380 to 415 V) 7m	1
Transformer Unit for Use Outside Japan (Internal type) Machine with.	1
Uninterruptible power supply (internal type) WithEnglish instruction	1
CO2 Injector (Internal Type) English manual	1
CO2 Injector (internal type)	1
Stayclean Injector	1
Stayclean Injector English manuals	1
KerlCenter Alignment	1
EMO Guard Ring	1
Usb Memory (Spare)	1
Stylus Pen Magnet Fixing Type	1
Melody Alarm	1
StainlessCover	1
Specification for preventing particles from adhering Atomizing noule	1
Specification for preventing particles from adhering Forced Exhaust F	1
Specification for preventing particles from adhering Spindle water cul	1
BraidedHose Joint ID IS.Omm x OD 22.0mm	2
Braided Hose ID 15.0 mm x OD 22.0mm	6
Water Temperature Control Unit OTU1550	1
Water Temperature Control Unit OTU1550 Power cable 7 m	1
Water Temperature Control Unit OTU1550 Piping Assy	1
Water temperature control unit (OTU1550) Digital flowmeter for chill	1
Water temperature control unit (OTU1550) Status indicator	1
Water temperature control unit (OTU1550) EMO guardring	1
Water temperature control unit (OTU1550) USB Memory	1